

*“Thanks For Choosing
Xtrack Outdoor Blinds”*

Your product must be correctly used, cared for, cleaned and maintained to insure longevity

*7 Year Manufacturers
Warranty*

Warranty Will Be Void if product is not correctly used, cared for cleaned and maintained

Contact us at

1300 704 480

justoutdoorblinds.com.au



**Xtrack Outdoor
Blinds**

*Creating Better Outdoor
Living For Your Family*

*Xtrack Blinds Are High Quality,
Easier to Use
and Maintain.*

Blind Effects PTY LTD trading as, Just
Outdoor Blinds, 38 Longview Court
Thomastown Victoria 3074

**Xtrack Outdoor
Blind System**

Correct Use.

- Take care while operating blinds on windy days. If blind stops while being lowered due to pressure on the side spline the operator can inadvertently cause the sidespline to be pulled out of its track.
- If the blind stops while being lowered it may be due to wind creating pressure on the side spline. Stop the blind and add some pressure downward to lower blind.
- Watch the blind while being lowered, if the blind gets caught on the tracks then stop the blind with the remote control. Check the tracks to check nothing is preventing the blind being lowered such as dirt, dust or grit.
- Just Outdoor Blinds use the strongest fabrics, fixings and extruded aluminium available, the operator should ensure blinds are not left down in extreme winds. “Blinds are made from fabric and extreme winds can cause fixings to snap, fabric stretch and tear and tracks to become loose from structure”

Creating a Better Lifestyle at Home

Cleaning

- Tracks must be regularly cleaned with soapy water so tracks are free from dirt dust and grit.
- Fabric can be cleaned with a mild detergent, sponge and hosed off with water.

Lubrication

- Tracks should be regularly lubricated with silicone spray.
- Spray tracks top to bottom with silicone, available from Bunnings or other hardware stores. **Warning Do Not Use an Oil Base** Lubricant, it will Damage the Side Spline

Maintenance

- If correctly used, cleaned and lubricated Xtrack blinds should be repair free for years to come.

Trouble Shooting

Side spline has come out of its track.

1. Remove bottom block from track
2. Remove screws from track face slide track down as far as possible
3. Remove top stop dome nut
4. Raise the blind to its highest position and feed the side spline back into the track like a zipper
5. One back in track lower the blind return track to original position and replace all fixings and blocks.
6. Consult correct use notes to ensure issue does not arise again.

Adjusting Limits to Motor

1. Visit Alpha Motors website, download universal motor instructions and follow instructions listed.
2. Reset limits as per instructions making sure you have finalised steps and new limits have been finalised.

Xtrack Outdoor Blinds

Proudly designed, manufactured and Installed by Just Outdoor Blinds. 38 Longview Court Thomastown Victoria 3074. Phone 03 9464 6312. justoutdoorblinds.com.au